


## Coaxial Cable Connector 25\_BNC-75-2-8/133\_N

### Description

Straight panel cable jack, flange mount

Interface standards

Interface compatible with IEC 61169-8



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 75 $\Omega$ |
| Interface frequency max. | 1 GHz       |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | crimped   |
| Outer contact  | crimped   |
| Weight         | 0.0168 kg |

#### Environmental Data

|  |                  |
|--|------------------|
| Operating temperature                                | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant        |

#### Material Data

| Piece Parts    | Material                 | Surface Plating                   |
|----------------|--------------------------|-----------------------------------|
| Centre contact | Copper Beryllium / Brass | Gold Plating (Nickel underplated) |
| Outer contact  | Brass                    | SUCOPLATE (R) Plating             |
| Body           | Brass                    | SUCOPLATE (R) Plating             |
| Insulator      | PFA / PTFE               |                                   |
| Crimp ferrule  | Copper                   | SUCOPLATE (R) Plating             |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00071040   |
| Catalogue drawing    | DCA-00008807   |
| Assembly instruction | DOC-0000179123 |

### Ordering Information

|                |                      |
|----------------|----------------------|
| Single package | 25_BNC-75-2-8/133_NE |
|----------------|----------------------|

### Additional Information

|                 |  |
|-----------------|--|
| Suitable cables | RG_179_B/U, ENVIROFLEX_179, RG_187_A/U |
|-----------------|--|

