## **Data Sheet**



# Coaxial Cable Connector 11\_BNC-75-3-11/133\_N

#### **Description**

Straight cable plug

Interface standards
Interface compatible with IEC 61169-8



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 75\,\Omega \\ \text{Interface frequency max.} & 1\,\text{GHz} \end{array}$ 

**Mechanical Data** 

Centre contact soldered
Outer contact clamped
Weight 0.0159 kg

**Environmental Data** 

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102) -65 °C to 165 °C compliant

#### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

#### **Related Documents**

Outline drawing DOU-00071342
Catalogue drawing DOU-00006639
Assembly instruction DOC-0000179064

### **Ordering Information**

Single package 11\_BNC-75-3-11/133\_NE

#### **Additional Information**

Suitable cables G\_03233\_D

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.